

PROCESS DESCRIPTION

available to totally isolate the site if a spill is detected to ensure that no further runoff can leave the area process continues until the water quality is suitable to be discharged to the stormwater system. An option is will close. If the next chamber of runoff is contaminated it will also be diverted to the holding tank. This contents will be diverted to a holding tank. After a short delay the system will reset and the Diversion Valve of a concentration that is not suitable to be discharged to stormwater an alarm will be activated and the pit conditions. Each time the pit fills the quality of the runoff is checked. If the level of pollutants in the runoff is sensor in the pit detects the presence of any dissolved pollutants and can be calibrated to match site until the cause of the alarm is addressed The Fox CMS600 system will monitor all site runoff for the presence of water soluble contaminants. A

System to be approved by relative Local Authorities

before Installation.


the purchaser.

authorities requirements. Tradesmen to be engaged by All plumbing and electrical connections to be installed by Slab size and gradient to engineers details as arranged

certified tradesmen in accordance with relative

by customer.

This is a schematic representation only.



Optional Control box

1200 x 650mm - Includes Bund Closure Valve.



270

This Drawing and design is the Property of Fox Environmental Systems Pty Ltd. It must not be used for any other purpose than that for which i Fox Environmental Systems Pty Ltd. lent to anyone without the written permission of was issued. This drawing must not be shown or

Project

System Specifications

Drawing Title

CMS600 System

Drawn by:	R.O'B.
Date:	8002/90/05
Scale:	1:20
Drawing No:	A4-SPEC-1011