Detail of CMS600 System

Model: CMS600

Manufacture: Fox Environmental Systems

Max Working Pressure:170 PSI Grate Class: Class D Heavy Duty **RPZ:** Compliant with ASSE1013

> Hardwire Supply cable to Fox Control Panel from Class 2 Power supply to avoid accidental disconnect of power supply

Placement of UPC Shield

Model: CMS 600 Manufacture: Fox Environmental Systems Max Working Pressure : 170 PSI Grate Class: Class B Heavy Duty RPZ: Compliant with ASSE1013

Must be protected by RPZ compliant with ASSE1013

IGC 234

or Equivalient

Class 2 Power

supply by others

0000000

Equal For Pipe Connections.

Model:- Mean Well LPF-60 Series

All washdown points must come from this point.

Control box. Contains PLC and

Demand Valve.

Drive Line (by others) ½"ØD Copper tube

24" C/O

6 core Control Cable Protect with 32mm conduit (by others)

IAPMO IGC 234 2016 File Number 10153

6"ø Outlet To Stormwater Sensor Probe Use 6 " Fernco 10566-66 or Equal For Pipe Connections. -Draw wing 6"ø Outlet -Fox Diversion Valve To Tradewaste

Use 6 " Fernco 10566-66 or

31 ½"

Plan View



Project

IAPMO

Drawing Title

CMS600 System

Drawn by:	J.F.S
Date:	15/08/2016
Scale:	1:20
Drawing No:	A4-SPEC-1011